


Geberit PE verloop centrisch, kort



Voorbeeldafbeelding

Toepassingsgebied

- Voor gebouwriolering
- Voor terreinriolering

Eigenschappen

- Centrisch

- UV-bestendig

Technische gegevens

Materiaal

PE-HD

Art. nr.	d, Ø	d1, Ø	H	h	K
360.557.16.1	40 mm	32 mm	8 cm	3 cm	1.5 cm
361.557.16.1	50 mm	32 mm	8 cm	3 cm	1.5 cm
361.559.16.1	50 mm	40 mm	8 cm	3 cm	1.5 cm
363.559.16.1	56 mm	40 mm	8 cm	3 cm	1.5 cm
363.560.16.1	56 mm	50 mm	8 cm	3 cm	1.5 cm
364.559.16.1	63 mm	40 mm	8 cm	3 cm	1.5 cm
364.560.16.1	63 mm	50 mm	8 cm	3 cm	1.5 cm
364.565.16.1	63 mm	56 mm	8 cm	3 cm	1.5 cm
365.559.16.1	75 mm	40 mm	8 cm	3 cm	1.5 cm
365.560.16.1	75 mm	50 mm	8 cm	3 cm	1.5 cm
365.565.16.1	75 mm	56 mm	8 cm	3 cm	1.5 cm
365.570.16.1	75 mm	63 mm	8 cm	3 cm	1.5 cm
366.559.16.1	90 mm	40 mm	8 cm	3 cm	1.5 cm
366.560.16.1	90 mm	50 mm	8 cm	3 cm	1.5 cm
366.565.16.1	90 mm	56 mm	8 cm	3 cm	1.5 cm
366.570.16.1	90 mm	63 mm	8 cm	3 cm	1.5 cm
366.575.16.1	90 mm	75 mm	8 cm	3 cm	1.5 cm
367.559.16.1	110 mm	40 mm	8 cm	3 cm	1.5 cm
367.560.16.1	110 mm	50 mm	8 cm	3 cm	1.5 cm
367.565.16.1	110 mm	56 mm	8 cm	3 cm	1.5 cm
367.570.16.1	110 mm	63 mm	8 cm	3 cm	1.5 cm
367.575.16.1	110 mm	75 mm	8 cm	3 cm	1.5 cm
367.580.16.1	110 mm	90 mm	8 cm	3 cm	1.5 cm
368.570.16.1	125 mm	63 mm	8 cm	3 cm	1.5 cm
368.575.16.1	125 mm	75 mm	8 cm	3 cm	1.5 cm
368.580.16.1	125 mm	90 mm	8 cm	3 cm	1.5 cm
368.585.16.1	125 mm	110 mm	8 cm	3 cm	1.5 cm